

Precision Clean

Multi-Purpose Cleaner/Degreaser



FEATURES

- Super industrial strength removes tough stains and soils
- Does not contain butyl, chlorinated or petroleum solvents, bleach, ammonia, or abrasives
- · Alkaline formula inhibits flash rusting
- · Rinses clean
- Safe on most surfaces (not for use with Magnesium & Aluminum)
- · VOC compliant in all 50 states
- Nonfood Compounds Program Listed

APPLICATIONS

- BilgesCarbon blocks
- TanksHoists
- Grease traps Exhaust hoods
- Tools
- CompressorsConcrete
- Machinery

Engines

- Garage floors
- Drill presses
- Sidewalks
- Driveways
- Ovens
- ,
- **SPECIFICATIONS AND APPROVALS**
- Ford Motor Co.
- NSF International, C1 Registration #168389 (Concentrate)
- NSF International, C1 Registration #059854 (RTU)

PACKAGING DETAILS

Part No. US	Part No. Canada	Part No. International	Net Contents	Container Type	Units/Case	Approximate Case Weight
02720	C02720		18 wt oz/510 g/525 mL - Ready-to-Use	aerosol	12	18 lbs
02728	C02728		28 fl oz / 828 mL - Ready-to-Use	trigger	12	27 lbs
02765	C02765		55 gal / 208 L - Ready-to-Use	drum	1	535 lbs
02701	C02701		1 gal / 3.78 L - Concentrate	bottle	4	38 lbs
02705	C02705		5 gal / 18.93 L - Concentrate	pail	1	46 lbs
02755	C02755	M02755	55 gal / 208 L - Concentrate	drum	1	535 lbs
		M02715	5 L - Concentrate	bottle	4	
		M02705	20 L - Concentrate	pail	1	
		M02728	750 mL - Ready-to-Use	trigger	12	



Precision CleanMulti-Purpose Cleaner/Degreaser

PROPERTIES	AEROSOL	CONCENTRATE	READY-TO-USE
Appearance/physical state	Gas	Liquid	Liquid
Odor	Citrus	Slight. Citrus.	Mild. Citrus.
Melting point/freezing point	Not available	28°F - 32°F (-2.2°C - 0°C)	28°F - 32°F (-2.2°C - 0°C)
Boiling point/range	200°F (93.33°C)	200°F (93.33°C)	200°F (93.33°C)
Vapor pressure	< 17.5 mm Hg @ 20°C	17.5 mm Hg @ 20°C (est.)	17.5 mm Hg @ 20°C (est.)
Percent volatile	Not available	Not available	96%
pH	12.7	13.4	12.7
Propellant	Petroleum Gases, Liquified	Not applicable	Not applicable
VOC Content	<8%	<0.5% based on 1:4 dilution	<0.5%
Color	Clear Blue	Blue	Clear Blue
Flash point	Not established	>200°F (93.33°C)	>200°F (93.33°C)
Density	8.4 lb/gal	8.70 lb/gal	8.4 lb/gal
Evaporation rate	1 BuAc	1 BuAc	1 BuAc
Vapor density	Not available	Heavier than air	Heavier than air
Viscosity	<3 cSt	Low viscosity comparable to water	Low viscosity comparable to water (water = 1 cSt @ 20°C)
Specific Gravity (water=1)	1.01	1.04	1.01
Solubility in Water	100%	100%	100%

FOR AEROSOL

DIRECTIONS

Shake well before using. Spray directly on surface to be cleaned. Allow foam to set 10 to 30 seconds. Wipe or rinse clean. Conductive (water-based). Do not use on energized equipment. If equipment is still dirty or greasy, repeat procedure.

HANDLING

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Avoid contact with eyes, skin, and clothing. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

STORAGE

Contents under pressure. Do not expose to heat or store at temperatures above 120°F/49°C as can may burst. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. Store in tightly closed container. Store in a well-ventilated place. Stored containers should be periodically checked for general condition and leakage. Store away from incompatible materials (see Section 10 of the SDS).

DISPOSAL INFORMATION

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Incinerate the material under controlled conditions in an approved incinerator. Dispose of contents/container in accordance with local/regional/national/international regulations.

FOR BULK

DIRECTIONS

(Dilute concentrate according to dilution chart below)
KEEP FROM FREEZING. MIX WELL BEFORE USING. Rinse and/or wipe dry
any residue. Test for compatibility on delicate materials.

DILUTION RATIO				
PRODUCT: WATER	EQUIPMENT			
1:4 - 1:6	Dip Tanks			
1:4 - 1:10	Basin-Style Parts Washers			
1:100	Trigger Sprayers			
1:5 - 1:8	Tumblers			
1:10 - 1:20	Ultrasonic Cleaners			
1:10 - 1:80	Pressure Washers			

HANDLING

Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. When using, do not eat, drink or smoke. Use only outdoors or in a well-ventilated area. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.

STORAGE

Store in tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

DISPOSAL INFORMATION

Collect and reclaim or dispose in sealed containers at licensed waste disposal site.