



REVO 66[®]

Contact Cleaner



FEATURES

- Ideal for removing dirt, moisture, flux, or oxides from the internal components of electronic equipment
- Quick, Penetration with no rinsing
- Non-Flammable/Fast Evaporation/Non-Conductive
- Does not contain brominated solvents; Unique alternative to HCFC cleaners
- NSF Certified: K2 Registration #140245
- VOC Compliant in all 50 states

APPLICATIONS

- Contacts
- Controls
- Instruments
- Meters
- Printed Circuit Boards
- Signals
- Switches
- Sensors
- Telecommunication Equipment

SPECIFICATIONS AND APPROVALS

- NSF International, K2

AVAILABLE PRODUCTS

Part No.		Net Contents	Container Type	Units/Case	Approximate Case Weight
US	Canada				
04416	C04416	12 wt oz / 340 g / 279 mL	aerosol	12	13 lbs

PROPERTIES

Appearance / Physical State	Gas
Color	Clear
Odor	Ether-like
Boiling Point / Range	< 131 °F (< 55 °C)
Flash Point	None
Water Solubility	Slight.
Density	11.06
Specific Gravity	1.33
VOC Content	74 %
Propellant	HFO-1234ze, carbon dioxide
Dielectric Strength	43.1 kV

DIRECTIONS

Hold can 6-8 inches away and spray directly on surface to clean. While safe to use on most surfaces, test for compatibility in an inconspicuous area before applying generally.

HANDLING

Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear eye/face protection.

STORAGE

Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight.

DISPOSAL

Dispose of contents/container in accordance to local/state/national waste disposal regulations.



CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!

800.241.8334 | www.itwprobrands.com

LPS[®], SCRUBS[®], DYKEM[®], Accu-Lube[®], DYMON[®], Spray Nine[®], and Cedar[®] are registered trademarks and Rustlick[™], Diamondkote[™], and MetalMates[™] are trademarks of Illinois Tool Works • All Rights Reserved